SGigE-E50-H2MC

5MP GigE CAMERA

www.sensing-world.com

GENERAL DESCRIPTION

The camera module adopts the HAITU CMOS HT50A image sensor, which features industrial-grade performance and is equipped with a C-Mount interface, enabling the connection of various lenses.



KEY PARAMETERS

Sensor	HAITU 5MP HT50A Mono
Image Size	2/3 inch CMOS
Shutter Mode	Rolling shutter
Output Pixels	2448H*2048V
Pixel Size	3.5um*3.5um
Frame Rate	23.5fps
Output Data	10bit
Region of Interest Mode	ROI
Camera Interface	GigE Vision
Transmission Rate	1000Mbit/s
Gain	0~64db
Shutter Time	1 ~ 5000000us
Trigger Mode	Software trigger, External trigger
Lens Mount	C-mount
Power Supply	DC12V±3V
Operating temp. range	0℃~+50℃
Storage temp. range	-20℃~80℃
Dimensions	W: 29mm, L:29mm, H:56.1mm
Weight	51g


Features

- High-speed output, maximum 120MB/s
- High sensitivity
- Wide dynamic range, low noise
- High stability
- Supports LABVIEW and HALCON visual development software
- External trigger/Software trigger
- Maximum cable length supported is 100m (can be infinitely extended on the broadcasting equipment)
- Can use standard NIC card
- Can use via Ethernet cable

Application

- Printed matter inspection
- Food processing inspection
- Fluid monitoring
- Wood and metal product inspection

DIMENSIONS



Note:

This icon indicates the imaging direction is positive.

ACCESSORIES

Accessory List			
Serial Number	Product Model	Quantity	Remarks
1	RJ45 - 5-meter Ordinary Sun Cable	1	Standard configuration
2	DC12V - 1A Power Adapter	1	Standard configuration
3	12-core M8 3M Camera Trigger Cable	1	Standard configuration



Revision History

Version	Description	Release date
Rev1	First Release	Oct.2025

Contact Us

SZ Sensing TECH CO.,LTD

HQ Address: 9/F,Gate 4,building 3,Specialized special new industrial park, No.16 Baolong 3rd Road， Baolong Street, Longgang District, Shenzhen

Phone: +86-755-28990915

Email： Sales@sensing-world.com

Company Website: www.sensing-world.com

WECHAT SKYPE WhatsApp